

HYDRAULIC OIL COOLER HC11

*Efficiency coupled with
performance*

The HC11 hydraulic oil cooler is constructed in lightweight aluminium. This unit has been specially designed with a slimline construction, making installation simple and very low maintenance, especially designed for the rigours of the transport environment.

Product features

- Temperature & level gauge
- 24V DC fan
 - Slim rear of cab design
 - Minimum installation requirement
 - Economic solution
 - Suction & Return Ports Both Sides
 - 3rd Line Drain Point



TRANSAIRVAC
INTERNATIONAL LTD

www.transairvac.com

HYDRAULIC OIL COOLER HC11

TECHNICAL SPECIFICATIONS

HC11 Cooler	
Hydraulic flow rate	100 litres/minute (max)
Hydraulic pressure	20 Bar (max)
Fan motor speed	3000 rpm
Heat dissipation	11.6 kW with 40°C differential
Oil Tank Capacity	13 litres
Noise	68 dB(A)
Dry Weight	15kg

FEATURES

- Aluminium construction
- Electric 24V DC cooling fan
- Thermostatically controlled
- Simple, reliable operation (no control valves)

Options:

- 12V DC Fan Motor
- Thermostatic Control

Also available: HC24



HC11 Cooler Dimensions



Other Transairvac products include:

- Hydraulic coolers
- Pressure line filters
- Compressors
- Vacuum pumps
- Blowers
- Rotary lobe pumps

TRANSAIRVAC
INTERNATIONAL LTD

Units 12 - 17, Croft road Industrial Estate,
Newcastle, Staffordshire ST5 0TW
Tel: +44 (0)1782 710282 Fax: +44 (0)1782 710126
email: office@transairvac.com
web: www.transairvac.com